

Service Module with 4 Redundant SFP GPON Ports for GPON Optical Concentrator Chassis FK-OLT-G2500

Description

Module with four GPON service ports with support for redundancy. The ports are arranged in pairs, and for each active port GPON there is also a corresponding redundant. Each 7U GPON Optical Concentrator can hold up to 10 modules.

General Characteristics

- 4 Ports with support to GPON standard;
- 4 Additional ports to support automatic redundancy
- Supports NSR and SR DBA (G.984.3);
- Supports ITU-T G.984.4 for Management and Control Interface (ONT OMCI);
- Remote management of ONT / MDU;
- Supports multiple T-conts per ONT;
- Supports up to 64 (max. 128) connections on a single fiber;
- Supports 2.5Gbps downstream and 1.25Gbps in upstream for each GPON port;
- Max logical transmission distance: 60Km.
- Supports transceivers SFP GPON classes B+ and C+;
- Supports type B redundâncy between GPON ports;

Constructive Characteristic

Dimensions (W x H x D): 348 mm x 18.5 mm x 260 mm

Warranty

1-year warranty

Related Products

35510177 OPTICAL CONCENTRATOR CHASSIS GPON FK-OLT-G1040 35510205 OPTICAL CONCENTRATOR CHASSIS GPON FK-OLT-G2500 35510197 OPTICAL TRANSCEIVER SFP OLT CLASS B+ FOR OPTICAL CONCENTRATOR

Codification



