



Service Module with 4 Redundant SFP GPON Ports for GPON Optical Concentrator Chassis FK-OLT-G2500

Description	Module with four GPON service ports with support for redundancy. The ports are arranged in pairs, and for each active port GPON there is also a corresponding redundant. Each 7U GPON Optical Concentrator can hold up to 10 modules.
General Characteristics	<ul style="list-style-type: none"> • 4 Ports with support to GPON standard; • 4 Additional ports to support automatic redundancy • Supports NSR and SR DBA (G.984.3); • Supports ITU-T G.984.4 for Management and Control Interface (ONT OMCI); • Remote management of ONT / MDU; • Supports multiple T-contrs per ONT; • Supports up to 64 (max. 128) connections on a single fiber; • Supports 2.5Gbps downstream and 1.25Gbps in upstream for each GPON port; • Max logical transmission distance: 60Km. • Supports transceivers SFP GPON classes B+ and C+; • Supports type B redundâncy between GPON ports;
Constructive Characteristic	<ul style="list-style-type: none"> • Dimensions (W x H x D): 348 mm x 18.5 mm x 260 mm
Warranty	1-year warranty
Related Products	35510177 OPTICAL CONCENTRATOR CHASSIS GPON FK-OLT-G1040 35510205 OPTICAL CONCENTRATOR CHASSIS GPON FK-OLT-G2500 35510197 OPTICAL TRANSCEIVER SFP OLT CLASS B+ FOR OPTICAL CONCENTRATOR

[Codification](#)